

TECNOCEMENTO



1. INTRODUCTION AND INFORMATION ABOUT TECNOCEMENTO®

Our company stands out for the reliability of its product and, first and foremost, for the quality of the projects where it has been applied. Renowned clients like the master pastry chef Francisco Torreblanca or the architect Tomás Amat have opted for TECNOCEMENTO® and placed their faith in our coating for their latest projects.

Applications at different restaurants, commercial premises and residential dwelling bear testimony to the excellent results achieved by TECNOCEMENTO® as well as the trust placed in us by a large number of architects, interior designers and decorators along with professional applicators the length and breadth of Spain.

Colour chart TECNOCEMENTO®

TECNOCEMENTO® is differentiated by the range of colours developed by our company. Grey as the flagship colour with reference to cement in a range with multiple tones.

In any case, a perfect control over the manufacturing process allows us to reproduce practically any colour customised to suit the client, based on a RAL chart or similar.



TECNOCEMENTO® VINTAGE SYSTEM applied in a bathroom of offices in Elche

2. TECNOCEMENTO® VINTAGE SYSTEM

TECNOCEMENTO® VINTAGE is our TECNOCEMENTO® coating, **APPLIED IN A SIMPLE SYSTEM THAT ALLOWS TO ADD TO OUR FLOORS AND VERTICAL CLOTHS, AN AGED PATINA BY TIME** together with the depth of the microcement's own texture.

The TECNOCEMENTO® VINTAGE system **is excellent for decorating “vintage” environments where you want to add a cement aged in time, pre-existing in moss green, asphalt and winter blues.**

TECNOCEMENTO® VINTAGE is an application of the **HOME, PLUS or IMPER SYSTEM**, depending on the support where we choose to apply, with a simple final modification in the application process where the “vintage texture” of our microcement is configured, according to the chosen colour.

The steps established for the application of the systems described above will be followed until the application of **PRIMER**. And, then the application process will be as follows:

Step 1. **TECNOCEMENTO® VINTAGE.** After the drying time of **PRIMER** layer has elapsed, **1 layer of VINTAGE** must be applied.

For the application of this layer, It has to be used **TECNOCEMENTO® 80/20'** but making a more liquid mixture. It will be used an sponge trowel (“talocha”) and a wet cloth to add the colour.

This layer has to be applied meter by meter, adding the colour using the sponge trowel (“talocha”) and “cleaning” the excess of the colour with the wet until the desired final texture is achieved.

Step 2. **TOP COATINGS.** It will be applied **2 layers** on the **PRIMER** layers once are completely dry.

The **TECNOCEMENTO® TOP COATINGS** provide a full naturalness to our systems, as well as a total impermeability (**FINISH FORTE or FINISH FORTE PLUS**).

A “**short-hair**” **microfiber roller** has to be used to “coat” properly the whole surface. It is a colourless product which highlights the final look of **TECNOCEMENTO®** systems.

***Drying times** depend on the **relative humidity, temperature and season of the year**. In case that you want to know drying times of any of our products, please, contact with our Technical Department (adrian@tecnoemento.com).

Calle Ramón Gorge, 44, bajo
03600 Elda (Alicante) España
Tel. +34 965 385 920
Fax +34 965 386 785

www.tecnocemento.com
info@tecnocemento.com