

TECNOCEMENTO



1. INTRODUCTION AND INFORMATION ABOUT TECNOCEMENTO®

Our company stands out for the reliability of its product and, first and foremost, for the quality of the projects where it has been applied. Renowned clients like the master pastry chef Francisco Torreblanca or the architect Tomás Amat have opted for TECNOCEMENTO® and placed their faith in our coating for their latest projects.

Applications at different restaurants, commercial premises and residential dwelling bear testimony to the excellent results achieved by TECNOCEMENTO® as well as the trust placed in us by a large number of architects, interior designers and decorators along with professional applicators the length and breadth of Spain.

Colour chart TECNOCEMENTO®

TECNOCEMENTO® is differentiated by the range of colours developed by our company. Grey as the flagship colour with reference to cement in a range with multiple tones.

In any case, a perfect control over the manufacturing process allows us to reproduce practically any colour customised to suit the client, based on a RAL chart or similar.



TECNOCEMENTO® METALLIC SYSTEM applied on a restaurant façade in San Juan

2. TECNOCEMENTO® METALLIC SYSTEM

TECNOCEMENTO® **METALLIC** is a system based on a combination of metallic pigments and acrylic resins that provides a completely different design and aesthetic look to the traditional coatings. **SYSTEM SUITABLE TO COAT VERTICAL SURFACES, FURNITURE, COUNTER TOPS** or any type of area where you want to reach a very personal touch.

TECNOCEMENTO® **METALLIC SYSTEM** allows combining its wide colour chart (gold, emerald, nacre, bronze, etc.) and its different finishes with any other material, offering a cheerful design and, of course, enhancing what is intended to prioritize, with a very original touch within the world of coatings.

TECNOCEMENTO® **METALLIC** is an application of the **HOME, PLUS or IMPER SYSTEM**, depending on the support where we choose to apply, with a simple final modification in the application process where the “vintage texture” of our microcement is configured, according to the chosen colour.

The steps established for the application of the systems described above will be followed **until the application of the 2nd layer of TECNOCEMENTO® 80/20'**, which will have to be mechanically sanded to get a flat and regularize surface. And, then the application process will be as follows:

Step 1. TECNOCEMENTO® **METALLIC. 1 layer** will be applied using the desired colour.

The metallic pigment will be previously mixed with an special acrylic resin. A spatula and flexible metallic trowel will be used to apply the colour on the surface.

It is recommended to **make small mixes and apply the product meter by meter**, adding colour to the coating with the trowel and spatula until the entire surface is covered with the desired colour.

Step 2. **TOP COATINGS.** It will be applied **2 layers** on the **PRIMER** layers once are completely dry.

The TECNOCEMENTO® **TOP COATINGS** provide a full naturalness to our systems, as well as a total impermeability (**FINISH FORTE or FINISH FORTE PLUS**).

A “**short-hair**” **microfiber roller** has to be used to “coat” properly the whole surface. It is a colourless product which highlights the final look of TECNOCEMENTO® systems.

***Drying times** depend on the **relative humidity, temperature and season of the year**. In case that you want to know drying times of any of our products, please, contact with our Technical Department (adrian@tecnocemento.com).

Calle Ramón Gorge, 44, bajo
03600 Elda (Alicante) España
Tel. +34 965 385 920
Fax +34 965 386 785

www.tecnocemento.com
info@tecnocemento.com